

INPUT SPECIFICATION		Options
1. Frequency range:	720 ± 200MHz, 720 ± 40MHz, 720 ± 20MHz (check model table)	
2. Connector:	BNC	TNC
3. Impedance:	50Ω	
4. Return loss:	≥15dB	≥20dB (*)
OUTPUT SPECIFICATION		
5. Frequency range:	8.0 to 9.0GHz (or any reduced part of this band)	
6. Connector:	N-type	SMA
7. Impedance:	50Ω	
8. Return loss:	≥20dB	
9. 1dB compression point:	+10dBm	
10. Third order intercept::	+20dBm	
TRANSFER CHARACTERISTICS		
11. Gain:	0 to 30dB, adjustable in 0.1dB steps	
12. Gain ripple:	over ±200MHz:	≤2dB p.t.p.
	over ±40MHz:	≤1dB p.t.p.
	over output band:	≤3dB p.t.p.
13. Group delay distortion:	over ±5MHz	<2ns
	over ±20MHz	<5ns
14. Gain stability, 0°C to 50°C:	±1dB	
15. Frequency stability, 0°C to 50°C:	2 x 10 ⁻⁷	Option 1: 10 ⁻⁷ Option 2: 10 ⁻⁸ Option 3: 3 x 10 ⁻⁹
16. External reference:	10MHz, 0dBm	5MHz, 0dBm
17. Synthesiser step size:	1MHz	
18. Noise figure (full gain):	<20dB	
Spurii		
19. Image rejection:	>75dB	
20. In-band spurii (at 0dBm output):	<-60dBc	
PHASE NOISE		
21. 10Hz:	<-45dBc/Hz	
22. 100Hz:	<-70dBc/Hz	
23. 1kHz:	<-80dBc/Hz	
24. 10kHz:	<-85dBc/Hz	
25. 100kHz:	<-95dBc/Hz	
26. 1MHz:	<-110dBc/Hz	
27. Mains related:	<-60dBc	
MISCELLANEOUS		
28. Power supply:	115V/230V ±10% 50/60Hz ±10%, 30VA	
29. Mechanical:	1U 19" frame, 400mm deep	
30. Temperature:	Operating:	0° to 50°C
	Storage:	-40° to 85°C
31. Relative humidity:	Operating:	0 to 90%
	Storage:	0 to 95%
32. Summary alarm:	NO and NC dry relay contacts via rear mounted connector	
33. Summary alarm indication:	Front panel LED	
34. Remote control:	RS232/RS485 serial interface	

(*) Noise figure increases by 3dB, overall gain decreases by 3dB.

MODEL TABLE

Output Frequency	Input frequency and bandwidth		
	700 ± 200MHz	720 ± 40MHz	720 ± 20MHz
8.0 - 9.0GHz	U688	U687	U686